

LTNG Test Connector, Right


MA013244

The **MA013244** LTNG Test Connector, Right, is an 8-pin single-sided test plug with straight signalling, designed for testing the Apple Lightning interface on mobile devices. A reliable, durable and highly accurate replacement for commercial cables and connectors.

All eight conductors are routed straight through (1:1) at 90 Ω dataline differential impedance. Power pins 1 and 5 carry up to 1.2 A; the remaining pins are rated 0.25 A. For the straight-exit variant, see **MA015028**.

The transmission of high data rates can be achieved — recommended to be verified in the applied test setup.

Designed for production testing, product development, repair and service centres, and laboratory use.



ELECTRICAL

Max. current (power, pins 1, 5)	1.2 A
Max. current (other pins)	0.25 A
Max. voltage	20 Vrms
Dataline diff. impedance	90 Ω
Operating temperature	0 – 60 °C
Storage temperature	–20 ... +70 °C
Relative humidity	15 – 95 % non-condensing

PINOUT

straight 1:1

Socket		Plug
1	→	1
2	→	2
3	→	3
4	→	4
5	→	5
6	→	6
7	→	7
8	→	8

OPTIONAL ACCESSORIES


MA085951 Float unit for the LTNG Test Connector — compensates for positional misalignment in automated test fixtures. Sold separately.

MECHANICAL

Mating force	6 N (typ.)
Unmating force	5 N (typ.)
Durability	50 000 cycles (typ.)
Compliance	RoHS

DIMENSIONS

mm



3D CAD models available on request via sales@bluelec.com